CLASS A AS/NZS 4233.1
PRESSURE CLEANER
NO RTO CERTIFICATION REQUIRED FOR OPERATORS

JETWAVE®

HIGH PRESSURE CLEANERS

HORNET™ G2 4060 psi • 15 l/pm

Petrol Driven | Cold Water | Daily Usage

FIELDS OF APPLICATION

Roof Cleaning
Painting Contractors
Cleaning Contractors
Boat Yards and Ports
Agricultural Equipment
Councils & Government

NEW JETWAVE G2 GENERATION
AUSTRALIAN OWNED & BUILT ESTABLISHED 1992
HONDA AUSTRALIA APPROVED

JETWAVE POWERED by HONDA™

HORNET G2 PRODUCT VIDEO

The Jetwave® Hornet G2™ revolutionises the single cylinder gearbox petrol driven cold water high pressure cleaner powered by HONDA™ Australian engineered and assembled; its innovation provides heavy duty users with a compact powerful, safe and easy to use unit that encompasses stainless steel exoskeleton (PEXO™) cover protection, centralised control & multi-configurable design.

HERO INNOVATIONS

Stainless Steel Exoskeleton (PEXO™)
Protective formed CNC cover to safeguard all components and for increased safety.

Multi Configuration
Industry first customisable modular build with precision heavy gauge steel chassis. Build it your way.

Centralised Control
Easily accessible one panel fascia mounted control(s) & components.

AVPS™
Anti-vibration protection system (AVPS™) for quieter & reliable performance.

Versatile
Multiple hose reel configurations.

STANDOUT FEATURES

- JW® Enhanced **Italian** triplex plunger pump delivers performance and longer life.
- **Low Speed** professional pump for increased reliability and longer maintenance intervals. (1450 RPM)
- **Pull start HONDA™ GX390** Industrial Series OHV Engine.
- Dual M22 screw hose coupling system.
- Heavy duty washable inlet water filter.
- **Jetwave Safety System™ (JSS)** thermal and safety valve to prevent overheating in excessive bypass and over pressurisation.
- Integrated accessory storage for gun and lance.
- Professional line accessories.
- Quality pressure gauge.
- **Zero** line pressure brass adjustable unloader valve.
- Emergency Stop.

Jetwave Group
10-16 Smith Street Thebarton I
Adelaide I South Australia I 5031 I AU
+61 8 8371 3599
sales@jetwave.com.au
jetwave.com.au

Compact - Modular frame design with top lift panels.

Protection - Designed for durability and a long life.

Control - Fascia mounted controls with plug n' go functionality.

Robust - Precision CNC frame.

Quality - Industry proven 'Italian' pump.

Power - Industrial OHV HONDA™ GX390 engine.

Flexibility - Multi configurable compact frame.

STANDARD EQUIPMENT

J5000™ Gun - with M22 swivel and extension.

Lance / Nozzle - Dual lance with variable pressure control complete with hardened nozzles.

Hose - 15m of 3/8" double wire braided hose with quick coupling(s).

OPTIONAL ACCESSORIES

High Pressure Swivel	p/n	Included
Additional High Pressure Hose (per metre)	p/n	52001
Complete Turbo Head with Lance	p/n	JWA160.04
LS12 Foaming Lance with Tank	p/n	JWA221-LS12
JW Pro Foam Bypass System	p/n	PROFOAM.04
OEM Hose Reel (30m Capacity) Pro Rapid Style Hose Reel (60m Capacity) Pro Rapid Stainless Steel Hose Reel (60m Capacity)	p/n p/n p/n	1060CMPL 1067CMPL 1067CMPLSS
Hammerhead™ FSC 21" - ABS Plastic	p/n	JWA-FSC21.04
Hammerhead™ FSC 21"- Stainless Steel	p/n	JWA-FSC22.04
Giraffe™ Alloy Telescopic Lance	p/n	JWA-TELE7.3.04
Sandblasting Kit	p/n	JWA164
Sludge Kit	p/n	80005
Drain Cleaning Hose	p/n	HOP2X15VF
Professional Drain Cleaning Kit	p/n	JWA-PDCK
Vulcan V1 Hot Box	p/n	10199

MACHINE OPTIONALS

Emergency Stop, Battery Isolator, 4 Wheel Trolley Kit	p/n	Included
Engine Hour Meter	p/n	TOL8075
5L Stainless Steel Chemical Holder	p/n	CHEM-5L

V2.0 08/2020

Product Code	p/n	CW4000-15PG2
TECHNICAL DATA		
Working Pressure	psi / bar	4060 / 280
Flow Rate	l/pm	15
Max Water Inlet Temp	°c / °f	60 / 140
Class (AS/NZS: 4233)	grade	A (4,200 BAR/LITRES)
INTENDED APPLICATION		
Usage Frequency	hours / type	4 Daily / Daily Usage
Category of Dirt / Debris	type	Medium
MOTOR FEATURES		
Engine	type	HONDA™ GX390 (4 stroke, air cooled)
Power	hp / cc	13 / 390
Fuel Supply	type	Unleaded
Fuel Capacity	litres	6.1
Low Oil Shutdown	y / n	Y
Hour Meter	y / n	N
Starting System	type	Pull Start
HYDRAULIC FEATURES		
Pump / Head / Pistons	type	JW® Italian Triplex Plunger/Brass (Nickle Plated)/Ceramic
Motor Pump Coupling	type	Gearbox Drive
Pump Speed	rpm	1450
Unloader Valve	type	Independent (Zero)
Safety Valve	y / n	Y
Orifice / Nozzle	size	04
OTHER FEATURES		
Adjustable Pressure	y / n	Y
Hose Reel Provision	y / n	Y
Frame Structure	type	CNC Modular skid with heavy gauge galvanised steel chassis plus satin powder coat finish and stainless steel cover
Onboard Accessory Storage	y / n	Y
Detergent Injector	y / n	Y - Downstream low pressure adjustable
DIMENSIONS & WEIGHT		
Approx Weight	kg	86 unit / 96 boxed
Unit Dimensions	mm	880(L) x 550(W) x 860(H)
Boxed Dimensions	mm	1200(L) x 800(W) x 1200(H)
Number per Pallet	type: pieces	Euro: 1
WARRANTY(S)		
Engine Warranty*	year(s)	3
Pump Warranty*	year(s)	2

*Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).
The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement.