



### A better design to reduce cleaning costs

Nilfisk SR 1601 is claimed to be the most technically advanced sweeper in its category, with innovations that increase cleaning productivity whilst simplifying operating and servicing requirements. Designed for industrial applications such as heavily soiled factories, construction sites, parking etc






The dust control, for example, is outstanding, and airborne particles are controlled more effectively thanks to the DustGuard™ system. And less dust means less cleaning elsewhere. Plus the productivity is excellent, thanks to a huge 900 mm main broom, a 1600 mm wide sweeping path, and the SR 1601s all around reliability for getting the job done quickly and well.

### PRODUCT FACTS

- Excellent machine manoeuvrability thanks to the power steering (STD)
- Nilfisk DustGuard™ system completely controls airborne dust to reduce cleaning time
- Free floating main broom and fine tuning knob adjustment increases productivity and performance
- MaxAccess™ system provides fast and easy access to facilitate servicing
- The strong yet lightweight rotomoulded polyethylene covers and bumpers over a steel chassis provide automobile industry quality protection
- NoTools™ system speeds main broom and side broom changing cutting down on service time

Model	SR 1601 D3	SR 1601 D3
Ref. no	13300101	13300148
Description	SWEeper SR 1601 D3	SWEeper SR 1601 D3 MAXI
<b>PRODUCT FEATURES</b>		
ADJUSTABLE STEERING		■
LEFT SIDE BRUSH PPL		■
POWER STEERING	■	■
<b>INCL. ACCESSORIES</b>		
33018855 BROOM MAIN CHEVRON UNION MIX	■	■
33017255 BROOM SIDE PPL 259X550	■	■
8-24-04139-1 FILTER PANEL	■	■

Technical specifications	SR 1601 D3	SR 1601 D3
MOTOR POWER SOURCE	Diesel, 3cyl. 19.4W (26hp)	Diesel, 3cyl. 19.4W (26hp)
MOTORBRAND	Kubota D1105	Kubota D1105
MAX SPEED (KM/H)	12	12
SOUND PRESSURE LEVEL (dB(A))	69.5	69.5
PRODUCTIVITY RATE THEORETICAL/ ACTUAL (M <sup>2</sup> /H)	12800/8960	12800/8960
WORKING WIDTH (MM)	900	900
WORKING WIDTH W/RIGHT SIDE BRUSH (MM)	1250	-
WORKING WIDTH W/2 SIDE BRUSHES (MM)	1600	1600
MIN. TURN-AROUND AISLE WIDTH (CM)	306	306
MAX CLIMBING RATE (%)	25	25
FUEL TANK ( L )	35	35
FUEL CONSUMPTION (L/H)	3.5	3.5
HOPPER VOLUME (L)	315	315
MAX DUMPING HEIGHT (CM)	159	159
MAIN FILTER AREA (CM <sup>2</sup> )	10	10
SIDE BROOM DIAMETER (MM)	550	550
LENGTH X WIDTH X HEIGHT (CM)	222x132x146	222x132x146
WEIGHT (KG)	945	980

Accessories		Ref. no	Min. required	SR 1601 D3
	<b>Broom cyl.</b>			
	BROOM MAIN CHEVRON NYLON 1.2	33018852	1	■
	BROOM MAIN CHEVRON PPL 0.5 WHITE NAVY	33018853	1	■
	BROOM MAIN CHEVRON PPL 0.5 WHITE NAVY/ST	33018854	1	■
	BROOM MAIN CHEVRON UNION MIX	33018855	1	■
	BROOM MAIN SPIRAL NYLON 1.2	33018856	1	■
	BROOM MAIN SPIRAL PPL 0.5WHITE NAVY	33018857	1	■
	BROOM MAIN SPIRAL PPL 0.5WHITE NAVY/STEE	33018858	1	■
BROOM MAIN SPIRAL UNION MIX	33018859	1	■	
	<b>Side brush</b>			
	BROOM SIDE PPL 259X550	33017255	1	■
	BROOM SIDE PPL 1.5/STEEL 0.35	33018889	1	■
	BROOM SIDE NYLON 0.5	33018890	1	■
BROOM LEFT SIDE KIT	33019173	1	■	
	<b>Filters</b>			
	FILTER POCKET 12V KIT	33019176	1	■
	POCKET FILTER WATER RESISTANT	56507740	1	■
	FILTER PANEL	8-24-04139-1	1	■
FILTER PANEL	8-24-04139-2	1	■	
	<b>Assembly</b>			
	GUARD OVERHEAD KIT	33019171	1	■
	STEERING ADJUSTABLE KIT	33019174	1	■
PRE MISTING SYSTEM KIT	33019175	1	■	
	<b>Others</b>			
	WHEEL SOLID KIT	33019139	1	■
	WHEEL SOLID NO MARKING KIT	33019172	1	■
	FIRE EXTINGUISHER KIT	56507027	1	■
MIRROR KIT FOR CAB AND OHG	56508663	1	■	