



IVC 60/30 Tact²

Compact industrial vacuum for cleaning manufacturing areas and production machinery. Suitable for continuous use thanks to the wear-resistant side channel compressor.



1 Wear-resistant side channel blower

- Filter designed to allow uninterrupted use with constant high suction power.

2 Wear-resistant side channel blower

- Filter designed to allow uninterrupted use with constant high suction power.

IVC 60/30 Tact²

- Antistatic equipment
- Liquid cut-off
- Integrated cyclone for pre-separation system

Technical data


Order No.	1.576-101.0	
EAN code	4039784463707	
Current type	Ph / V / Hz	3 / 400 / 50
Air flow	l/s / m³/h	68 / 244.8
Vacuum	mbar / kPa	286 / 28.6
Container capacity	l	60
Rated input power	kW	3
Filter area	m²	1.9
Nominal size	DN 70	
Accessory nominal size	DN 50 / DN 40	
Sound level	dB(A)	77
Weight	kg	95
Dimensions (L x W x H)	mm	970 × 690 × 1240

Equipment

Accessories included	No
-----------------------------	----

IVC 60/30 TACT²

1.576-101.0



		Order No.	Quantity	ID	Length	Width	Price	Description	
Flat pleated filter, paper									
Flat pleated filter	1	6.907-276.0	1 piece(s)					Flat pleated filter dust class M, nano-coated paper. Suitable for fine dust and dry dirt pick up.	<input type="checkbox"/>
Flat pleated filter, PTFE									
	2	6.907-449.0	1 piece(s)						<input type="checkbox"/>