SC800 is designed for maximum performance, easy handling, low maintenance, superb cleaning results and yet it is an eco-friendly solution. SC800 walk-behind scrubber dryer is designed for heavy-duty cleaning but is easy to handle and flexible in every day cleaning situations. It is ideal for routine cleaning from ultra light to heavy scrubbing such as entryways, spill cleanup, grease removal, grout and porous-surface cleaning. SC800 can clean with water only for detergent residue removal. Combined with a new squeegee concept SC800 provides more effective water collection, and together with the powerful vacuum motor ensures that the floor dries quickly.

SC800 walk-behind scrubber dryer for heavy-duty cleaning

- Powerful brush and vac motors, high down pressure (up to 77 kg), outstanding cleaning and drying performance: the best answer for heavy duty "industrial "task
- Green oriented: complete consumption control: Ecoflex<sup>™</sup> system, low noise level (only 61dB(A))
- Large 95 litre solution and recovery tanks give extra capacity for longer working time
- The scrub deck is protected with removable covers that prevent
  damage to walls and doors, while providing easy access for maintenance
- · Right industrial shape in compact dimensions. No compromise on the ergonomic level and maneuverability



Picture shown may not represent model quoted

#### • Standard equipment

Included ac	ccessories	Ref. no.	Min. required	SC800-71	SC800-86	SC800-71C
Squeegee Blade						
BLADE KIT-SQUE	EGEE GUM	56112330	1	•		
BLADE KIT-SQUE	EGEE LINATEX	56112331	1			•
Other						
KIT-REFILLING HO	DSE	56112355	0	•	•	•
Model			SC800-71	SC80	00-86	SC800-71C
Ref. no.			56112034	5611	2035	56112036
PRODUCT FEATURES						
Disc brush version			•		•	
Front and rear bumpers			•		•	•
Cylindrical brush version						•
Interchangeable brush deck			•	•	•	•
Adjustable brush pressure			•	•	•	
Click on-off brush			•	•	•	
One touch control panel			•		•	•
Compact squeegee concept			•		•	•
Debris tray			•		•	•
Ecoflex prepared			•		•	•



Ref. no.661120345611203556112035PRODUCT FEATURES•••Solution tank with easy drain system•••Removable plastic deck covers•••Builtin squeegee hanger•••Squeege••••Technical specificationsSC800-71SC800-86SC800-71Maximum running time3.53.53.5Max. specif (m/h)5.85.8S.8Voltage (V)2.42.42.4IP protection classIIIIIIIIIRated power (W)180018001800Brush motor (W)2.6502.5502.550Traction motor power (W)300300300Vacuum (IPa)12.812.812.8Sound pressure level (dB(A))616161Output pressure level (dB(A))12.512.512.5South notor power (M)12.512.512.5Sound pressure level (dB(A))616161Sound pressure level (dB(A))616161Productivity theoretical actual (m?h)12.512.512.5Southon/recovery tank (I)35736753695Southonge with (min)161161161Productivity theoretical actual (m?h)12.512.5Southon pressure (leve)36773677361South pressure (leve)3677367536455South pressure (leve)367	Model	SC800-71	SC800-86	SC800-71C
Solution tank with easy drain system••Removable plastic deck covers••Built-in squeegee hanger••Squeegee••Technical specificationsSC200-71SC200-86SC200-71CMaximum running time3.53.53.5Max. speed (rm/h)5.85.85.8Voltage (V)2.42.41.9JP protection classIIPIIIIIIIlp notection classIIIIIIIIIRated power (W)199018901910Brush motor (W)2.65502.85502.5560Traction notor power (W)300300300Vacuum notor power (W)300300300Vacuum notor power (W)300300300Vacuum (kPa)12.812.812.8Sound pressure level at 1.5 m (dB(A) ISO 3744)616161Productivity theoretcal' actual (m <sup>2</sup> h)222Vacubing rate (%)2222Vacubing rate (%)212.512.5501450Squeegee width (mm)102.5140.512.612.5Subject (RPM)3677367736360Squeegee width (mm)35575430432-5Subject (RPM)2702708401400-780Start for (Imm)3637736773636Squeegee width (mm)1400-780-11301400-780-11301400-780-1130Start for (	Ref. no.	56112034	56112035	56112036
Removable plastic deck coversBuilt in squeegee hangerSqueegeeSqueegeeTechnical spacificationsSC800-71SC800-87Maximum running time.3.5.3.5.3.5.Max speed (km/h).5.8.5.8.5.8.5.8Voltage ().24.24.24.IP ordection class	PRODUCT FEATURES			
Bullin squeegee hanger••Squeegee•••Technical specificationsSC800-71SC800-86SC800-71Maximum running time3.53.53.5Max: speed (km/h)5.85.85.8Veltage (V)2.42.42.4IP protection classIP MAIPX4IPX4Insulation classIIIIIIIIIRated power (W)189019101010Brush motor (W)2.5552.55502.5550Traction motor power (W)300300300Actuum motor power (W)300300300Youcum (kac)303030Youcum (kac)303030Sound pressure level (dS(A))6161Sound pressure level (dS(A))6161Sound pressure level (dS(A))112.512.5Sounding rate (%)222Vater flow (im)150.54304.42-Sounding rate (%)27020012.5Solution/recover park (i)355/3554304.42-Sounding rate (%)270270440Brush paged (RPM)356/3554304.42-Sounding rate (km)366/77366/7736Sounding rate (km)255/352.52.5Sounding rate (km)12.512.5-Sounding rate (km)135354/354.304.32Sounding rate (km)13536.4-Sounding	Solution tank with easy drain system	•	•	•
Squeege••Technical specificationsSC800-71SC800-86SC800-71Maximum running timeS.5S.5S.5Maximum running timeS.5S.5S.5Voltage (Mr/h)S.8S.8S.8Voltage (Mr/h)242424P protection classIPX4IPX4IPX4Insulation classIIIIIIIIRated power (W)189018901910Brush motor (W)2x5502x5502x560Traction motor power (W)300300300Vacuum motor power (W)490490490Arlow (I/sec.)303030Vacuum motor power (W)616161Sound pressure level (dB(A))616161Sound pressure level (dB(A))616161Sound pressure level (dB(A))7108202x500Scubbing rate (%)2222Soution/recovery tank (I)95959595595955Squeegee width (mn)9101050910Brush pressure (kg)36773677367Brush pressure (kg)202022Suth pressure (kg)202022Suth pressure (kg)202022Brush pressure (kg)202022Brush pressure (kg)148074801130144074801313144074801413Brush pressure (kg)161161616	Removable plastic deck covers	•	•	•
Technical specifications         SC800-71         SC800-71         SC800-71           Maximum running time         3.5         3.5         3.5           Max. speed (mr/h)         5.8         5.8         5.8           Voltage (V)         24         24         24           P protection class         III         III         III         III           Rated power (W)         1890         1890         1910           Brush motor (W)         2x550         2x550         2x560           Traction motor power (W)         300         300         300           Vacuum motor power (W)         440         440         440           Vacuum motor power (W)         300         300         300           Vacuum (kPa)         12.8         12.8         12.8           Sound pressure level (dB(A))         5374         41202470         4202470           Productivity theoretical' actual (m?h)	Built-in squeegee hanger	•	•	•
Maximum nuning time         3.5         3.5         3.5           Max. speed (km/h)         5.8         5.8         5.8           Voltage (V)         24         24         24           IP protection class         IPX4         IPX4         IPX4           Insulation class         III         III         III           Rated power (W)         1890         1890         1910           Brush motor (W)         2x550         2x550         2x560           Traction motor power (W)         300         300         300           Vacuum motor power (W)         300         300         300           Vacuum motor power (W)         30         30         30           Vacuum motor power (W)         30         30         30           Vacuum motor power (W)         30         30         30           Vacuum (kPa)         12.8         12.8         12.8           Sound pressure level at 1.5 m (dB(A) ISO 3744)         61         61         61           Sound pressure level at 1.5 m (dB(A) ISO 3744)         12.5         12.5         12.5           Soutobing width (mm)         12.5         12.5         12.5         12.5           Soutobing reac (%)         2	Squeegee	•	•	•
Max. speed (km/h)5.85.85.8Voltage (V)242424IP protection classIPX4IPX4IPX4Insulation classIIIIIIIIIRated power (W)199018901910Brush motor (W)2x5502x5502x560Traction motor power (W)300300300Vacuum motor power (W)300300300Vacuum motor power (W)303030Vacuum motor power (W)303030Vacuum motor power (W)303030Vacuum (kPa)12.812.812.8Sound pressure level (dB(A))616161Sound pressure level (dB(A))616161Sound pressure level (dB(A))12.512.512.5Sourbing width (mm)710860710Max. climbing rate (%)222Vater flow (l/m)12.512.512.5Soutoin/recovery tank (I)95/9595/9595/95Squege width (mm)9101050910Brush paed (RPM)270270640Brush paed (RPM)1480x780x11301480x780x1130Brush paed (RPM)1480x780x11301480x780x1130Brush paed (RPM)1480x780x11301480x780x1130Brush paed (RPM)1480x780x11301480x780x1130Brush paed (RPM)1480x780x11301480x780x1130Brush paed (RPM)166x362x362616x362x362Brush paed (	Technical specifications	SC800-71	SC800-86	SC800-71C
Voltage (v)         24         24         24         24           IP protection class         IP X4         IP X4         IP X4           Insulation class         III         III         III           Rated power (W)         1890         1890         1910           Brush motor (W)         2x550         2x550         2x560           Traction motor power (W)         300         300         300           Vacuum motor power (W)         490         490         490           Airflow (I/sec.)         30         30         30           Vacuum (KPa)         12.8         12.8         12.8           Sound pressure level (dB(A))         61         61         61           Sound pressure level at 1.5 m (dB(A) ISO 3744)         61         61         61           Productivity theoretical/ actual (m?/h)         4120/2470         4990/2990         4120/2470           Scrubbing width (mm)         710         860         710           Max. climbing rate (%)         2         2         2           Scrubing vidth (mm)         910         155         51/355         430/432         -           Brush/pad Idameter (mm)         55/355         430/432         -	Maximum running time	3.5	3.5	3.5
IP protection class         IPX4         IPX4         IPX4           Insulation class         III         III         III           Rated power (W)         1890         1890         1910           Brush motor (W)         2x550         2x550         2x560           Traction motor power (W)         300         300         300           Vacuum motor power (W)         490         490         490           Airflow (I/sec.)         30         30         30           Vacuum (kPa)         12.8         12.8         12.8           Sound pressure level (dB(A))         61         61         61           Sound pressure level (dB(A))         4120/2470         4990/2990         4120/2470           Sound pressure level (dB(A))SO 3744)         61         61         61           Sound pressure level (dB(A))SO 3744)         61         61         61           Sound pressure level (dB(A))SO 3744)         710         860         710           Sound pressure level (dB(A))SO 3744)         112.5         1/2.5         1/2.5           Sound pressure level (dB(A))SO 3744)         910         1050         95/95           Sound pressure level (dB(A))SO 3744)         910         12.5         1/2.5 <t< td=""><td>Max. speed (km/h)</td><td>5.8</td><td>5.8</td><td>5.8</td></t<>	Max. speed (km/h)	5.8	5.8	5.8
Insulation classIIIIIIRated power (W)189018901910Brush motor (W)2x5502x5602x560Traction motor power (W)300300300Vacuum motor power (W)490490490Airflow (I/sec.)303030Vacuum (kPa)12.812.812.8Sound pressure level (dB(A))616161Sound pressure level (dB(A)) ISO 3744)616161Productivity theoretical actual (m²h)4120/24704990/29904120/2470Scrubbing width (mm)710860710Max. climbing rate (%)222Solution/recovery tank (I)95/9595/9595/95Squeegee width (mm)35/355430/432-Brush pressure (kg)36/7736/7736Brush pressure (kg)20 isc2 Disc2 CignidicalBrush pressure (kg)20 isc2 Disc2 CignidicalBrush pressure (kg)1480/780x11301480x780x11301480x780x1130Brush pressure (kg)1480x780x11301480x780x11301480x780x1130Brush pressure (kg)16i616161Brush pressure (kg)16020 isc2 CignidicalBrush pressure (kg)1480x780x11301480x780x11301480x780x1130Brush pressure (kg)16i616x362x362616x362x362Gright K width x height (mm)1616x362x362616x362x362616x362x362Weight (kg)<	Voltage (V)	24	24	24
Raded power (W)         1890         1890         1890         1890         1890           Brush motor (W)         2x550         2x560         2x500           Yacuum motor power (W)         300         300         300           Airdiow (I/sec.)         30         30         30           Yacuum motor power (MEA)         12.8         12.8         12.8           Sound pressure level (dB(A))         61         61         61           Sound pressure level (dB(A))SO 3744)         61         61         61           Yorducivity theoretical actual (m <sup>2</sup> /h)         4120/2470         4990/2990         4120/2470           Sound pressure level dB(A) ISO 3744)         710         860         710           Sound pressure level dB(A) ISO 3744)         710         860         710           Sound pressure level dB(A) ISO 3744)         710         860         710           Sound pressure level dB(M)         710         860         710           Max. cimbing rate (%)         2         2         2           Soution/recovery tank (I)         95/95         95/95         95/95           Squeege width (mm)         355/355         430/432         -           Brush speed (RPM)         270         2 </td <td>IP protection class</td> <td>IPX4</td> <td>IPX4</td> <td>IPX4</td>	IP protection class	IPX4	IPX4	IPX4
Bush motor (W)         2x550         2x560         2x560           Traction motor power (W)         300         300         300           Vacuum motor power (W)         490         490         490           Airflow (I/sec.)         30         30         30           Vacuum (kPa)         12.8         12.8         12.8           Sound pressure level (dB(A))         61         61         61           Sound pressure level (dB(A))SO 3744)         61         61         61           Productivity theoretical actual (m <sup>2</sup> /h)         4120/2470         4990/2990         4120/2470           Scrubing width (mm)         710         860         710           Max. climbing rate (%)         2         2         2           Scrubing width (mm)         1/2.5         1/2.5         1/2.5           Solution/recovery tank (I)         95/95         95/95         95/95           Squeegee width (mm)         910         1050         910           Brush pressure (kg)         36/77         36/77         36           Brush speed (RPM)         270         2         2           Brush quantity and type         2 Disc         2 Cylindrical           Length x width x height (mm)         1480X	Insulation class	Ш	Ш	Ш
Traction motor power (W)         300         300           Vacuum motor power (W)         490         490         490           Airflow (I/sec.)         30         30         30           Vacuum (kPa)         12.8         12.8         12.8           Sound pressure level (dB(A))         61         61         61           Sound pressure level (dB(A)) ISO 3744)         61         61         61           Productivity theoretical/ actual (m*/h)         4120/2470         4990/2990         4120/2470           Scrubbing width (mm)         710         860         710           Max. climbing rate (%)         2         2         2           Vater flow (I/m)         11/2.5         11/2.5         11/2.5           Solution/recovery tank (I)         95/95         95/95         95/95           Squeegee width (mm)         355/355         430/432         -           Brush pressure (kg)         36/77         36/77         36           Brush speed (RPM)         2 Disc         2 Disc         2 Cylindrical           Length x width x height (mm)         1480x780x1130         1480x780x1130         1480x780x1130           Brush quantity and type         2 Disc         2 Cylindrical         1490         1490	Rated power (W)	1890	1890	1910
Vacuum motor power (W)         490         490         490           Airflow (I/sec.)         30         30         30           Vacuum (kPa)         12.8         12.8         12.8           Sound pressure level (dB(A))         61         61         61           Sound pressure level at 1.5 m (dB(A) ISO 3744)         61         61         61           Productivity theoretical/ actual (m²/h)         4120/2470         4990/2990         4120/2470           Scrubbing width (mm)         710         860         710           Max. climbing rate (%)         2         2         2           Vater flow (I/m)         1/2.5         1/2.5         1/2.5           Solution/recovery tank (I)         95/95         95/95         95/95           Squeegee width (mm)         1050         910         910           Brush pressure (kg)         36/77         36/77         36           Brush speed (RPM)         2Disc         2 Disc         2 Cylindrical           Brush quantity and type         2Disc         2 Disc         2 Cylindrical           Length x width x height (mm)         1480x780x1130         1480x780x1130         1480x780x1130           Brush quantity and type         2Disc         2 Disc	Brush motor (W)	2x550	2x550	2x560
Airflow (l/sec.)3030Vacuum (kPa)12.812.812.8Sound pressure level (dB(A))616161Sound pressure level at 1.5 m (dB(A) ISO 3744)616161Productivity theoretical/ actual (m?h)4120/24704990/29904120/2470Scrubbing width (mm)710860710Max. climbing rate (%)222Vater flow (l/m)1/2.51/2.51/2.5Solution/recovery tank (l)95/9595/9595/95Squeegee width (mm)9101050910Brush/pad diameter (mm)36/7736/7736Brush pressure (kg)36/7736/7736Brush speed (RPM)210sc2 Disc2 CylindricalLength x width x height (mm)1480x780x11301480x780x11301480x780x1130Brutery compartment size (LxWxH) (mm)616x362x362616x362x362616x362x362Weight (kg)169170174Gross weight (gwy) (kg)487488492	Traction motor power (W)	300	300	300
Vacuum (kPa)         12.8         12.8         12.8           Sound pressure level (dB(A))         61         61         61           Sound pressure level at 1.5 m (dB(A) ISO 3744)         61         61         61           Productivity theoretical/ actual (m²/h)         4120/2470         4990/2990         4120/2470           Scrubbing width (mm)         710         860         710           Max. climbing rate (%)         2         2         2           Vater flow (l/m)         1/2.5         1/2.5         1/2.5           Solution/recovery tank (l)         95/95         95/95         95/95           Squeegee width (mm)         910         1050         910           Brush pressure (kg)         36/77         36/7         36           Brush speed (RPM)         20         2         2         2           Brush speed (RPM)         20 isc         2 Disc         2 Cylindrical           Brush speed (RPM)         1480x780x1130         1480x780x1130         1480x780x1130           Brush speed (RPM)         1480x780x1130         1480x780x1130         1480x780x1130           Brush speed (RPM)         1480x780x1130         1480x780x1130         1480x780x1130           Brush speed (RPM)         1480x780x113	Vacuum motor power (W)	490	490	490
Sound pressure level (dB(A))         61         61         61         61           Sound pressure level at 1.5 m (dB(A) ISO 3744)         61         61         61         61           Productivity theoretical/ actual (m²/h)         4120/2470         4990/2990         4120/2470           Scrubbing width (mm)         710         860         710           Max. climbing rate (%)         2         2         2           Vater flow (l/m)         1/2.5         1/2.5         1/2.5           Solution/recovery tank (l)         95/95         95/95         95/95           Squeegee width (mm)         910         1050         910           Brush pressure (kg)         36/77         36/77         36           Brush speed (RPM)         20 bisc         2 Disc         2 Cylindrical           Brush speed (RPM)         1480x780x1130         1480x780x1130         1480x780x1130           Brush speed (RPM)         2 Disc         2 Disc         2 Cylindrical           Brush quantity and type         2 Disc         2 Disc         2 Cylindrical           Brush speed (RPM)         1480x780x1130         1480x780x1130         1480x780x1130           Brush speed (RPM)         1616x362x362         616x362x362         616x362x362      <	Airflow (l/sec.)	30	30	30
Sound pressure level at 1.5 m (dB(A) ISO 3744)         61         61         61         61           Productivity theoretical/ actual (m²/h)         4120/2470         4990/2990         4120/2470           Scrubbing width (mm)         710         860         710           Max. climbing rate (%)         2         2         2           Water flow (l/m)         1/2.5         1/2.5         1/2.5           Solution/recovery tank (l)         95/95         95/95         95/95           Squeegee width (mm)         910         1050         910           Brush/pad diameter (mm)         355/355         430/432         -           Brush pressure (kg)         36/77         36/77         36           Brush speed (RPM)         2 Disc         2 Disc         2 Cylindrical           Length x width x height (mm)         1480x780x1130         1480x780x1130         1480x780x1130           Battery compartment size (LxWxH) (mm)         616x362x362         616x362x362         616x362x362           Weight (kg)         169         170         174           Gross weight (gvw) (kg)         487         488         492	Vacuum (kPa)	12.8	12.8	12.8
Productivity theoretical/ actual (m²/h)         4120/2470         4990/2990         4120/2470           Scrubbing width (mm)         710         860         710           Max. climbing rate (%)         2         2         2           Vater flow (l/m)         1/2.5         1/2.5         1/2.5           Solution/recovery tank (l)         95/95         95/95         95/95           Squeegee width (mm)         910         1050         910           Brush/pad diameter (mm)         355/355         430/432         -           Brush pressure (kg)         36/77         36/77         36           Brush speed (RPM)         2         2         2         2           Length x width x height (mm)         1480x780x1130         1480x780x1130         1480x780x1130           Battery compartment size (LxWxH) (mm)         616x362x362         616x362x362         616x362x362           Weight (kg)         169         170         174           Gross weight (gvw) (kg)         487         488         492	Sound pressure level (dB(A))	61	61	61
Scrubbing width (mm)         710         860         710           Max. climbing rate (%)         2         2         2           Water flow (l/m)         1/2.5         1/2.5         1/2.5           Solution/recovery tank (l)         95/95         95/95         95/95           Squeegee width (mm)         910         1050         910           Brush/pad diameter (mm)         355/355         430/432         -           Brush pressure (kg)         36/77         36/77         36           Brush speed (RPM)         270         20         20           Brush speed (RPM)         2 Disc         2 Disc         2 Cylindrical           Length x width x height (mm)         1480x780x1130         1480x780x1130         1480x780x1130           Battery compartment size (LxWxH) (mm)         6163c32s362         6163c32s362         6163c32s362           Weight (kg)         169         170         174           Gross weight (gvw) (kg)         487         488         492	Sound pressure level at 1.5 m (dB(A) ISO 3744)	61	61	61
Max. climbing rate (%)         2         2         2           Water flow (I/m)         1/2.5         1/2.5         1/2.5           Solution/recovery tank (I)         95/95         95/95         95/95           Squeegee width (mm)         910         1050         910           Brush/pad diameter (mm)         355/355         430/432         -           Brush pressure (kg)         36/77         36/77         36           Brush speed (RPM)         270         840         1           Brush quantity and type         2 Disc         2 Cylindrical         1           Length x width x height (mm)         1480x780x1130         1480x780x1130         1480x780x1130           Battery compartment size (LxWxH) (mm)         616x362x362         616x362x362         616x362x362           Weight (kg)         169         170         174           Gross weight (gvw) (kg)         487         488         492	Productivity theoretical/ actual (m²/h)	4120/2470	4990/2990	4120/2470
Water flow (I/m)         1/2.5         1/2.5         1/2.5           Solution/recovery tank (I)         95/95         95/95         95/95           Squeegee width (mm)         910         1050         910           Brush/pad diameter (mm)         355/355         430/432         -           Brush pressure (kg)         36/77         36/77         36           Brush speed (RPM)         270         840         36           Brush quantity and type         2 Disc         2 Cylindrical         1480x780x1130         1480x780x1130           Battery compartment size (LxWxH) (mm)         616x362x362         616x362x362         616x362x362           Weight (kg)         169         170         174           Gross weight (gwy) (kg)         488         492	Scrubbing width (mm)	710	860	710
Solution/recovery tank (I)95/9595/9595/95Squeegee width (mm)9101050910Brush/pad diameter (mm)355/355430/432-Brush pressure (kg)36/7736/7736Brush speed (RPM)270270840Brush quantity and type2 Disc2 Disc2 CylindricalLength x width x height (mm)1480x780x11301480x780x11301480x780x1130Battery compartment size (LxWxH) (mm)616x362x362616x362x362616x362x362Weight (kg)169170174Gross weight (gvw) (kg)487488492	Max. climbing rate (%)	2	2	2
Squeegee width (mm)         910         1050         910           Brush/pad diameter (mm)         355/355         430/432         -           Brush pressure (kg)         36/77         36/77         36           Brush speed (RPM)         270         270         840           Brush quantity and type         2 Disc         2 Disc         2 Cylindrical           Length x width x height (mm)         1480x780x1130         1480x780x1130         1480x780x1130           Battery compartment size (LxWxH) (mm)         616x362x362         616x362x362         616x362x362           Weight (kg)         169         170         174           Gross weight (gvw) (kg)         487         488         492	Water flow (I/m)	1/2.5	1/2.5	1/2.5
Brush/pad diameter (mm)       355/355       430/432       -         Brush pressure (kg)       36/77       36/77       36         Brush speed (RPM)       270       270       840         Brush quantity and type       2 Disc       2 Disc       2 Cylindrical         Length x width x height (mm)       1480x780x1130       1480x780x1130       1480x780x1130         Battery compartment size (LxWxH) (mm)       616x362x362       616x362x362       616x362x362         Weight (kg)       169       170       174         Gross weight (gvw) (kg)       487       488       492	Solution/recovery tank (I)	95/95	95/95	95/95
Brush pressure (kg)       36/77       36/77       36         Brush speed (RPM)       270       270       840         Brush quantity and type       2 Disc       2 Disc       2 Cylindrical         Length x width x height (mm)       1480x780x1130       1480x780x1130       1480x780x1130         Battery compartment size (LxWxH) (mm)       616x362x362       616x362x362       616x362x362         Weight (kg)       169       170       174         Gross weight (gvw) (kg)       487       488       492	Squeegee width (mm)	910	1050	910
Brush speed (RPM)270270840Brush quantity and type2 Disc2 Disc2 CylindricalLength x width x height (mm)1480x780x11301480x780x11301480x780x1130Battery compartment size (LxWxH) (mm)616x362x362616x362x362616x362x362Weight (kg)169170174Gross weight (gvw) (kg)487488492	Brush/pad diameter (mm)	355/355	430/432	-
Brush quantity and type2 Disc2 Disc2 CylindricalLength x width x height (mm)1480x780x11301480x780x11301480x780x1130Battery compartment size (LxWxH) (mm)616x362x362616x362x362616x362x362Weight (kg)169170174Gross weight (gvw) (kg)487488492	Brush pressure (kg)	36/77	36/77	36
Length x width x height (mm)         1480x780x1130         1480x780x1130         1480x780x1130           Battery compartment size (LxWxH) (mm)         616x362x362         616x362x362         616x362x362           Weight (kg)         169         170         174           Gross weight (gvw) (kg)         487         488         492	Brush speed (RPM)	270	270	840
Battery compartment size (LxWxH) (mm)         616x362x362         616x362x362         616x362x362           Weight (kg)         169         170         174           Gross weight (gvw) (kg)         487         488         492	Brush quantity and type	2 Disc	2 Disc	2 Cylindrical
Weight (kg)         169         170         174           Gross weight (gvw) (kg)         487         488         492	Length x width x height (mm)	1480x780x1130	1480x780x1130	1480x780x1130
Gross weight (gvw) (kg) 487 488 492	Battery compartment size (LxWxH) (mm)	616x362x362	616x362x362	616x362x362
	Weight (kg)	169	170	174
	Gross weight (gvw) (kg)	487	488	492
Net weight (kg) 169 170 174	Net weight (kg)	169	170	174



ullet Standard equipment,  $^{\bigcirc}$  Supplementary accessories,  $^{\square}$  Mountable equipment

Accessories		Ref. no.	Min. required	SC800-71	SC800-86	SC800-71C
Disc Brush 4	30 mm					
	DISC BRUSH-17 AGLITE 3 LUG	56505783	2			
	DISC BRUSH-17 DYNAGRIT 3 LUG	56505782	2			
	DISC BRUSH-17 MAGNAGRIT 3 LUG	56505781	2			
	DISC BRUSH-17 MIDGRIT 3 LUG	56505787	2			
	DISC BRUSH-17 MIDLITE 3 LUG	56505788	2			
	DISC BRUSH-17 PROLENE 3 LUG	56505784	2			
	DISC BRUSH-17 PROLITE 3 LUG	56505785	2			
	DISC BRUSH-17 UNION MIX 3 LUG	56505786	2			
Special Pad						
	PAD 14 355MM ECO BRILLIANCE BLUE 2PCS	10002325	2	0		
	PAD 14 355MM ECO BRILLIANCE GREEN 2PCS	10002327	2	0		
	PAD 14 355MM ECO BRILLIANCE RED 2PCS	10002324	2	0		
	PAD 14 355MM ECO BRILLIANCE YELLOW 2PCS	10002326	2	0		
Ó	PAD 17 432MM ECO BRILLIANCE BLUE 2PCS	10002337	2		0	
Ó	PAD 17 432MM ECO BRILLIANCE GREEN 2PCS	10002339	2		o	
Ó	PAD 17 432MM ECO BRILLIANCE RED 2PCS	10002336	2		o	
Ó	PAD 17 432MM ECO BRILLIANCE YELLOW 2PCS	10002338	2		0	
Pad 14" / 35	5 mm					



	Accessories	Ref. no.	Min. required	SC800-71	SC800-86	SC800-71C
lacksquare	PAD 14 355MM ECO BLUE 5PCS	10001917	0	0		
lacksquare	PAD 14 355MM ECO BROWN 5PCS	10001918	0	0		
lacksquare	PAD 14 355MM ECO GREEN 5PCS	10001919	0	0		
0	PAD 14 355MM ECO RED 5PCS	10001920	0	0		
	PAD 14 355MM ECO REMOVER 5PCS	10001977	1	0		
0	PAD 14 355MM ECO WHITE 5PCS	10001921	0	0		
Battery						
	BATT.24V-220AH GEL SINGLE CELLS IN TRAY	L00210012	1			
	BATT.24V-240AH WET TRAY WITH AQUAMATIC	L00290018	1			
	BATT. 6V-175Ah WET Tubular Monobloc	80563211	4	0		
and the second sec	BATT. 6V-180AH GEL MONOBLOC	80564000	4			
	BATT. 6V-240AH GEL MONOBLOC	80564100	4			
	BATT. 6V-255AH WET SEMI T MONOBLOC	80565000	4		D	D
Ecoflex Syste	m					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	1			
	KIT-CHEMICAL INJECTION EU	56112244	1			
Brush Cylind	ical					
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	2			
	BRUSH HARD NYLON 28-NATURAL	56412192	2			D



	Accessories	Ref. no.	Min. required	SC800-71	SC800-86	SC800-71C
	BRUSH POLYPROPYLENE 28-RED	56412046	2			
	BRUSH SOFT NYLON 28-YELLOW	56412191	2			
Disc Brush 3						
	DISC BRUSH-14 AGLITE 3 LUG	56505803	2			
	DISC BRUSH-14 DYNAGRIT 3 LUG	56505802	2			
	DISC BRUSH-14 MAGNAGRIT 3 LUG	56505801	2			
	DISC BRUSH-14 MIDGRIT 3 LUG	56505807	2			
	DISC BRUSH-14 MIDLITE 3 LUG	56505808	2			
	DISC BRUSH-14 PROLENE 3 LUG	56505804	2			
	DISC BRUSH-14 PROLITE 3 LUG	56505805	2			
	DISC BRUSH-14 UNION MIX 3 LUG	56505806	2			
Light Option						
	KIT-LASER	56112138	1			
Pad 17" / 432	2 mm					
0	PAD 17 432MM ECO BLUE 5PCS	10001939	0		0	
0	PAD 17 432MM ECO GREEN 5PCS	10001940	0		0	
0	PAD 17 432MM ECO RED 5PCS	10001941	0		o	
	PAD 17 432MM ECO REMOVER 5PCS	10001978	1		0	
0	PAD 17 432MM ECO WHITE 5PCS	10001936	0		o	
Squeegee B	lade					
	BLADE KIT-SQUEEGEE GUM	56112330	1	•		
	BLADE KIT-SQUEEGEE LINATEX	56112331	1			•
	BLADE KIT-SQUEEGEE PU	56112332	1			
Other						
	KIT-MOP HOLDER	56112312	1			



	Accessories	Ref. no.	Min. required	SC800-71	SC800-86	SC800-71C
	KIT-REFILLING HOSE	56112355	0	•	•	•
	KIT-VAC WAND WITH TOTE BAG	56112141	1			
	KIT-WET FLOOR HOLDER	56112140	1			
	UTILITY CADDY	56112222	1			
External Char	ger					
	CHARGER HF 24V 20A SB175R	80522421	1	0	0	0
	CHARGER HF 24V 25A SB175R	80542426	1	0	0	0
Pad Holder		:				
	PAD HOLDER-14 3 LUG	56505800	2			
	PAD HOLDER-17 3 LUG	56505780	2			
Battery and Charger						
	PROGRAMMER WITH CABLE	56112255	1			
On-Board Charger						
	KIT-ON BOARD CHARGER-EU	56112245	1			

